

ZOOM II / Laser OWL Test Kit

SKU: KIT-Z2-L2xx (see connector options below)

Singlemode Fiber Test Kit
Netcomp Part No. FK03

Overview

The **ZOOM II / Laser OWL Test Kit** is ideal for LAN managers and installers who need to do simple attenuation tests on their singlemode networks.

The **ZOOM II** is an economical fiber optic power meter. It provides accurate testing of singlemode fiber cables. The 4-digit 7-segment LCD displays power readings with a resolution of 0.01dB. On-screen indicators display measurement units (dBm, dB, uW), as well as battery life. The ZOOM II comes configured with a 2.5mm universal connector for connection to ST or SC connectors, as well as any other fiber connector with a 2.5mm ferrule.

The **Laser OWL** is a 1310/1550nm NIST traceable singlemode light source. Its dual wavelength outputs are temperature-stabilized for accurate measurements. The Laser OWL has three connector options: ST, SC, or FC.

Kit Contents

- Power Meter:** ZOOM II
- Light Source:** Laser OWL
- Accessories:** Product manuals
9-volt batteries
NIST certificate
Carrying case
Protective rubber boots



Features

- Economical option for quick attenuation and loss testing singlemode networks
- Easy-to-read 4-digit 7-segment LCD display
- Store reference values for calibrated wavelengths
- Intuitive 2-button interface on both units
- On-screen wavelength, measurement units, and low battery indicator
- NIST traceable



MADE IN USA

N.I.S.T. Traceable

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.

Carrying cases and patch cables are available for an additional charge. Call 262-473-0643 for more information.



o.w.l. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>

ZOOM II / Laser OWL Test Kit

SKU: KIT-Z2-L2xx (see connector options below)

Singlemode Fiber Test Kit

Specifications

ZOOM II Optical Power Meter

Detector	Ge 1mm
Calibrated Wavelengths	850nm, 1300, 1310nm, 1550nm
Measurement Range	+5 to -60 dBm
Accuracy	±0.2 dBm
Resolution	0.10 dBm
Battery Life	up to 250 hours
Operating Temperature	0 to 55°C
NIST Traceable	Yes
Battery Capacity Display	Yes
Connector	2.5mm Universal
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

Laser OWL Singlemode Laser Source

Launch Method	FP Laser
Connector	ST, SC, or FC
Center Wavelength (1310nm)	1310 ±30nm
Center Wavelength (1550nm)	1550 ±30nm
Spectral Width (FWHM; 1310 / 1550 nm)	2 nm
Output Power	-10.0 dBm
Initial Accuracy	0.1 dB
Fiber Type	singlemode
Battery Life	25 hours
Battery Capacity Display	Yes
Operating Temperature	0 to 55° C
Storage Temperature	0 to 75° C
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.



o.w.l. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>