

AT-GS950/16

16 Port Gigabit WebSmart Switch



AT-GS950/16-xx

16 port 10/100/1000T Websmart Switch with 2 SFP Combo Ports

Performance

Allied Telesyn's WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. This WebSmart switch provides a network manager some key features using the simple web-based management function such as; port based Vlan's, 802.1p QoS, port trunking/link aggregation, port mirroring, priority queue's & 802.1x security support. With support of up to 8K MAC addresses & a 512K packet buffer GS950/16 WebSmart switch is an ideal option for integrating management into your network solution.

Value

Never thought you could afford managed switches in your network? Always wanted to provide management functionality at the edge? Now's your chance. Allied Telesyn's WebSmart switch truly helps network managers get the most value for their dollar. With industry standard protocols, fiber media support via the SFP's and simple plug n play usability right out of the box how can you go wrong implementing this cost-effective solution into your network?

Quality & Reliability

Allied Telesyn is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesyn offers proven reliability and industry recognized quality. Every unmanaged switch is backed with a lifetime limited warranty.

Key Features

- 16 10/100/1000TX Ports
- 2 SFP Combo ports
- Non-Blocking Architecture
- Auto MDI/MDIX
- Web Based Management
- 802.1x Security
- Up to 8K MAC addresses
- Port-Based VLAN's (up to 64 groups)
- Link Aggregation
- Port Setting (Speed, Availability, Flow Control)
- Port-Trunking
- Port Mirroring
- 802.1p QoS
- Login ID/Password
- Statistics & Diagnostics
- RS232 CLI Interface
- Rackmount Kit
- Limited Lifetime Warranty

AT-GS950/16 | 16 Port Gigabit WebSmart Switch

Performance

14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps Ethernet
1,488,000pps for 1000Mbps Ethernet

MAC Addresses 8K

Packet Buffer 512KB

Power Characteristics

Voltage 100-240vAC
Frequency 50/60Hz
Current 0.3A

Interface Connections

10/100/1000TX RJ-45
1000FX (SFP) 1000SX or 1000LX

Environmental Specifications

Operating Temp. 0°C to 40°C
(32°F to 104°F)
Non-operating Temp. -25°C to 70°C
(-13°F to 158°F)
Operating Humidity 5% to 90% non-condensing
Storage Humidity 5% to 95% non-condensing

Technical Specifications

Physical Characteristics

Dimensions 35.2 x 25.6 x 4.32 cm
(13.9 x 8.5 x 1.7 in)

Weight 2.38 kg (5.25 lbs)

Wall-mount or Desktop

All units come with Wall & 19" Rack mount brackets

Standards & Compliance

IEEE802.3	CSMA/CD
IEEE802.3u	100 Base Tx
IEEE802.3z	1000 Base SX
IEEE802.3z/ab	1000 Base T
IEEE802.3x	Flow-Control
IEEE 802.1p	Prioritization (4 queues)
IEEE802.1x	Authentication
IEEE802.1d	Bridging
IEEE802.3ad	Link Aggregation

Electrical/Mechanical Approvals

UL 1950
FCC/EN55022 Class A
VCCI Class A
C-Tick
EN60950 (TUV)
EN55024
CE

Ordering Information

AT-GS950/16-xx
16 port 10/100/1000T Websmart Switch
with 2 SFP Combo Ports

Where xx = 10 for U.S. power cord
= 20 for no power cord
= 30 for U.K. power cord
= 40 for Australia power cord
= 50 for Europe power cord

Product Contents

Switch unit
RS232 cable
Rackmount/wall mount brackets & screws
Power Cord
User Manual/Install guide on CD
Rubber feet

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesyn.com

© 2006 Allied Telesyn Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000105 Rev. C

AT-GS950/24

24 Port Gigabit WebSmart Switch



AT-GS950/24-xx

24 port 10/100/1000T Websmart Switch with 2 SFP Combo Ports

Performance

Allied Telesyn's WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. This WebSmart switch provides a network manager some key features using the simple web-based management function such as; port based Vlan's, 802.1p QoS, port trunking/link aggregation, port mirroring, priority queue's & 802.1x security support. With support of up to 8K MAC addresses & a 512K packet buffer GS950/24 WebSmart switch is an ideal option for integrating management into your network solution.

Value

Never thought you could afford managed switches in your network? Always wanted to provide management functionality at the edge? Now's your chance. Allied Telesyn's WebSmart switch truly helps network managers get the most value for their dollar: With industry standard protocols, fiber media support via the SFP's and simple plug n play usability right out of the box how can you go wrong implementing this cost-effective solution into your network?

Quality & Reliability

Allied Telesyn is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesyn offers proven reliability and industry recognized quality. Every unmanaged switch is backed with a lifetime limited warranty.

Key Features

- 24 10/100/1000TX ports
- 2 SFP Combo ports
- Non-Blocking Architecture
- Auto MDI/MDIX
- Web Based Management
- 802.1x Security
- Up to 8K MAC addresses
- Port-Based VLAN's (up to 64 groups)
- Link Aggregation
- Port Setting (Speed, Availability, Flow Control)
- Port-Trunking
- Port Mirroring
- 802.1P QoS
- Login ID/Password
- Statistics & Diagnostics
- RS232 CLI Interface
- Rackmount Kit
- Limited Lifetime Warranty

AT-GS950/24 | 24 Port Gigabit WebSmart Switch

Performance

14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps Ethernet
1,488,000pps for 1000Mbps Ethernet

MAC Addresses 8K

Packet Buffer 512KB

Power Characteristics

Voltage 100-240vAC
Frequency 50/60Hz
Current 0.3A

Interface Connections

10/100/1000TX RJ-45
1000FX (SFP) 1000SX or 1000LX

Environmental Specifications

Operating Temp. 0°C to 40°C
(32°F to 104°F)
Non-operating Temp. -25°C to 70°C
(-13°F to 158°F)
Operating Humidity 5% to 90% non-condensing
Storage Humidity 5% to 95% non-condensing

Technical Specifications

Physical Characteristics

Dimensions 44.0 x 25.7 x 4.32 cm
(17.3 x 10.1 x 1.7 in)

Weight 3.24 kg (7.15 lbs)

Wall-mount or Desktop

All units come with Wall & 19" Rack mount brackets

Standards & Compliance

IEEE802.3	CSMA/CD
IEEE802.3u	100 Base Tx
IEEE802.3z	1000 Base SX
IEEE802.3z/ab	1000 Base T
IEEE802.3x	Flow-Control
IEEE 802.1p	Prioritization (4 queues)
IEEE802.1x	Authentication
IEEE802.1d	Bridging
IEEE802.3ad	Link Aggregation

Electrical/Mechanical Approvals

UL 1950
FCC/EN55022 Class A
VCCI Class A
C-Tick
EN60950 (TUV)
EN55024
CE

Ordering Information

AT-GS950/24-xx
24 port 10/100/1000T Websmart Switch
with 2 SFP Combo Ports

Where xx = 10 for U.S. power cord
= 20 for no power cord
= 30 for U.K. power cord
= 40 for Australia power cord
= 50 for Europe power cord

Product Contents

Switch unit
RS232 cable
Rackmount/wall mount brackets & screws
Power Cord
User Manual/Install guide on CD
Rubber feet

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesyn.com

© 2006 Allied Telesyn Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000104 Rev. C

AT-GS950/48

48 port Gigabit WebSmart Switch



AT-GS950/48-xx

48 port 10/100/1000T WebSmart switch with 4 SFP combo ports

Performance

Allied Telesis' WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. This WebSmart switch provides a network manager some key features using the simple web-based management function such as; port-based VLANs, IEEE 802.1p QoS, port trunking/link aggregation, port mirroring, priority queues and IEEE 802.1x security support. With support of up to 8K MAC addresses and a 512K packet buffer the AT-GS950/48 WebSmart switch is an ideal option for integrating management into your network solution.

Value

Never thought you could afford managed switches in your network? Always wanted to provide management functionality at the edge? Now's your chance. Allied Telesis' WebSmart switch truly helps network managers get the most value for their dollar. With industry standard protocols, fiber media support via the SFP's and simple Plug and Play usability right out of the box how can you go wrong implementing this cost-effective solution into your network?

Quality and Reliability

Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesis offers proven reliability and industry recognized quality.

Key Features

VLAN

- IEEE 802.1Q tagged
- Port-based
- Up to 64 groups

Quality of Service Classification

- IEEE 802.1p tagging
- Port-based priority
- Four priority queues per port

IP Multicast Support (IPv4)

- IGMP snooping (v1/v2)
- Static multicast group
- Spanning-Tree, IEEE 802.1d/w

IEEE 802.3ad Link Aggregation

- Manual

IEEE 802.1x Port-based and MAC-based Network Access Control

- Local authentication server (MD5 only)
- Remote authentication through RADIUS
- Dynamic VLAN assignment

- RADIUS client for IEEE 802.1x

- DHCP client

- Statistics charts in Web

- Jumbo frames - up to 9K

Others

- IEEE 802.3x flow control or *HOL blocking Prevention (*when flow control is off)
- Port mirroring
- Destination MAC filtering
- Ingress/egress rate limiting
- Broadcast storming control

Management Features

Window-based Supporting

- Switch discovery management up to 254 switches
- Monitor list
- Trap view
- Device setting
- Firmware upgrade by FTP and Web
- Configuration back-up/restore by FTP
- Factory reset
- Password access control and restricted IP access list
- SNMPv1/v2c

MIBs

- RFC 1213 MIB-II
- RFC 1643 Ethernet MIB
- RFC 1493 Bridge MIB
- Private Enterprise MIB (Allied Telesis provides the spec)

RMON Groups (1, 2, 3, 9)

- Stats
- History
- Alarms
- Events

AT-GS950/48 | 48 port Gigabit WebSmart Switch

Performance

14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps Ethernet
1,488,000pps for 1000Mbps Ethernet

MAC addresses	8K
Packet buffer	512KB
DRAM	32M
Flash	4M

Power Characteristics

Voltage 100-240V AC
Frequency 50/60Hz

Interface Connections

10/100/1000T RJ-45
SFP 1000SX or 1000LX

Environmental Specifications

Operating temp. 0°C to 40°C
(32°F to 104°F)
Non-operating temp. -25°C to 70°C
(-13°F to 158°F)
Operating humidity 5% to 90% non-condensing
Storage humidity 5% to 95% non-condensing
Vibration IEC 68-2-36
Shock IEC 68-2-29
Drop IEC 68-2-32

Technical Specifications

Physical Characteristics

Dimensions 44.4cm x 32.2cm x 4.35cm
17.5" x 12.7" x 1.7"

Weight 4.05kg (8.92 lbs)

Wall-mount or Desktop

All units come with wall / 19" rack-mount brackets

Standards and Compliance

IEEE 802.3	CSMA/CD
IEEE 802.3i	10T
IEEE 802.3u	100TX
IEEE 802.3z	1000SX/LX
IEEE 802.3z/ab	1000T
IEEE 802.3x	Flow control
IEEE 802.1p	Prioritization (four queues)
IEEE 802.1x	Authentication
IEEE 802.1d	Bridging
IEEE 802.3ad	Link aggregation
IEEE 802.1Q	Tagged VLAN
IEEE 802.1d/w	Spanning-Tree Rapid Spanning-Tree

Electrical/Mechanical Approvals

UL 1950
FCC/EN55022 Class A
VCCI Class A
C-Tick
EN60950 (TUV)
EN55024
CE
CSA / CUL

MTBF

263,000 hours
Bellcore TR332

Ordering Information

AT-GS950/48-xx

48 port 10/100/1000T WebSmart switch
with 4 SFP combo ports

Where xx = 10 for US power cord
20 for no power cord
30 for UK power cord
40 for Australian power cord
50 for European power cord

Product Contents

Switch unit
Rack-mount brackets and screws
Power cord
User manual/install guide on CD
Rubber feet

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000217 Rev. C