



AT-9000/24

Layer 2 Managed Gigabit Ethernet Switch

AT-9000/24

24 port 10/100/1000T managed Gigabit Ethernet switch with RJ-45 connection and 4 SFP combo slots

Delivering Performance and Scalability

With up to 35.7Mpps throughput and supporting up to 255 VLANs the AT-9000/24 is a powerful entry level managed switch. This layer 2 gigabit Ethernet switch enables administrators to extend networks via four mini GBICs (SFP) slots. The SFPs are plug and play and hot swappable.

Flexibility

Ideally suited for small and medium businesses, hotels, schools and universities. The AT-9000/24 switch offers 24 copper ports and 4 combo SFP for uplinks.

Richly equipped with features normally found on higher-priced products the AT-9000/24 switch supports RADIUS, security with 802.1x authentication, VLAN tagging and more. Bandwidth hungry networks can streamline traffic with the four priority queues found in the IEEE 802.1p prioritization feature. And high traffic points can be addressed with the IEEE 802.1ad link aggregation and LACP feature supporting.

Management

Although a plug-and-play device, the AT-9000/24 switch included an extensive range of management feature such as WEB-based interfaces, command line interfaces, SNMP and Telnet.

Management is available though any tagged or untagged VLAN and firmware and configuration files may be uploaded or downloaded via TFTP. The AT-9000/24 switch can be used on a desktop or in a rack. The switch is MDI/MDI-X on all ports for simple connection to other hubs and switches. Front panel LEDs allow users to monitor the switch status providing simple "at a glance" management.

Key Features

- SNMP v1 and v2
 - Telnet remote login
 - Non blocking architecture
 - Wire-speed performance
 - Rapid Spanning Tree
 - RADIUS
 - Four priority queues per port
 - VLAN tagging
 - Port Mirroring
 - Link Aggregation - LACP*
 - SNTP*
 - GVRP*
- * future release

AT-9000/24 | Layer 2 Managed Gigabit Ethernet Switch

Technical Specifications

Performance

Wire speed switching on all Ethernet ports up to 1000Mbps throughput
14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps fast Ethernet
1,488,000pps for 1000Mbps Gigabit Ethernet

Switching capacity 24Gbps
Throughput 48Gbps

Store and forward mode
Non blocking switch fabric
Full Wire Speed
Head of line blocking prevention
Broadcast Storm Control

MAC address up to 8k
VLANs 255
GVRP*
Half/Full Duplex
Auto negotiation
Auto MDI/MDI-X on all ports

RAM
20MB divided into:
4MB Image storage Memory
16MB Dynamic Memory
Packet Buffer Memory: 2Mbit

Reliability

MTBF 200,000+ hrs
MTTR <1/2 hr DoA<1%

Interface Connections

10/100/1000TX RJ-45
RS232 DB9 pin, male port
Internal power supply

Power Characteristics

Voltage 100- 240vAC
Current 1.5A
Power Consumption 38W Maximum
Frequency 50-60Hz

Environmental Specifications

Operating Temp 0°C to 45°C (32F to 113F)
Storage Temp -25°C to 70°C (-13F to 158F)
Relative Humidity 10% to 90% non-condensing
Storage Humidity 5% to 95% non-condensing
Operating Altitude Maximum 3,000m (9,843ft)

Physical Characteristics

W x D x H 440mm x 387mm x 44mm
17.32" x 15.24" x 1.73"
Weight 3.25kg (7.16lbs)
Mounting 19" rack-mountable
hardware included

Standards and Compliance

802.1D Spanning Tree Protocol
802.1W Rapid Spanning Tree
802.1p Class of Service
802.1Q VLAN Tagged VLAN
802.1x Port-based network access control
802.3i 10Base-T Ethernet
802.3ab 100base-T
802.3ac VLAN tag frame extension
802.3ad Link aggregation, LACP*
802.3u 100base-T Ethernet
802.3x Back pressure/ flow control
802.3af Data Terminal Equipment (DTE) via Media Dependent Interface (MDI)
802.3z 1000SX
RFC 1112 IGMP snooping v1.0/ v2.0
RFC 2865 RADIUS
RFC 783 TFTP

SNMP Standards

RFC 1157 SNMPv1/v2
RFC 1213 MIB-II
RFC 1215 TRAP MIB
RFC 1493 Bridge MIB
RFC 1757 RMON 4 groups:
stats, history, alarms, events
RFC 2674 802.1QMIB
Allied Telesis managed switch MIB

Management Standards

Web interface – Multiple sessions can be supported at the same time
Console command line interface
SNMP compatibility
Telnet remote login – Multiple sessions can be supported at the same time
Port Mirroring
Dual software images
RFC 2030 SNMP*

Electrical/Mechanical Approvals

Safety UL 1950 (UL/cUL), EN60950 (TUV)
EMI FCC Class A, EN55022 Class A, VCCI Class A, COTick, EN61000-3-2, EN61000-3-3
Immunity EN55024

Country of Origin

China

Ordering Information

AT-9000/24-xx
24-port 10/100/1000TX managed switch with 4 combo SFPs

Where xx = 10 for US
= 30 for UK
= 40 for Australia
= 50 for Europe

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2006 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000086-00 Rev.H